



RTH 5.23 rotating telescopic handler

Referencia: RTH 5.23

Description

It has pivoting stabilisers to guarantee the safety and stability of all the manoeuvres carried out in industrial sectors and construction work.

Includes a Deutz 136 hp TCD 3.6 L4 Phase IV motor. It has 360° rotation. With a 100% pressurised cabin that facilitates the operator's vision, it includes an easy-to-use multifunction screen. It has automatic accessory detection through the RFID system, which creates the corresponding load diagrams. The accessories are interchangeable throughout the range.

The RTH 5.23 Smart handlers includes

- 360° rotation
- 3-in-1 Handler that can adapt as a crane, forklift and basket
- Registered design cabin
- FOPS/ROPS certification
- MCTS system: Touch screen with diagnostics
- 100% air filtration.
- Standard heating and air conditioning
- Cup holder
- RFID accessory recognition system
- Four wheel drive
- Automatic levelling
- Electrical system in CAN Bus

- Optimal lifting performance
- Gradeability 30°/44°

Technical sheet

| | |
|--------------------------------------|------------------------------|
| Model | RTH 5.23 |
| Engine type | Deutz TCD 3,6 L4 - Stage V |
| Length | 7180 mm |
| Width | 2550 mm |
| Weight | 16400 kg |
| Load capacity | 5000 kg |
| Height Elevation | 23 m |
| Maximum range | 19.5 m |
| Motor Power (KW) | 100 kW (136 hp) at 2,200 rpm |
| Maximum elevation height | 22.8 m |
| Stabilizers | Pivoting |
| Load capacity at maximum height | 2200 kg |
| Ground clearance | 320 mm |
| No. of gears | 44959 |
| Hydraulic system | 350 bar |
| Travel speed | 40 km/h |
| Rotation | 360° (continued) |
| Climate control as standard | Yes |
| Automatic recognition of accessories | Yes |
| Ordering | 4999 |