



RTH 5.25 rotating telescopic handler

Referencia: RTH 5.25

Description

It has standard stabilisers to guarantee the safety and stability of all the manoeuvres carried out in industrial sectors and construction work.

Includes a Deutz 136 hp TCD 3.6 L4 Phase IV motor. It has 360° rotation. With a 100% pressurised cabin that facilitates the operator's vision, it includes an easy-to-use multifunction screen. It has automatic accessory detection through the RFID system, which creates the corresponding load diagrams. The accessories are interchangeable throughout the range.

The RTH 5.25 Smart handler includes

- 360° rotation
- 3-in-1 Handler that can adapt as a crane, forklift and basket
- Registered design cabin
- FOPS/ROPS certification
- MCTS system: Touch screen with diagnostics
- 100% air filtration.
- Standard heating and air conditioning
- Cup holder
- RFID accessory recognition system
- Four wheel drive

- Automatic levelling
- Electrical system in CAN Bus
- Optimal lifting performance
- Gradeability 34°/58°

Technical sheet

Engine type	Deutz TCD 3,6 L4 - Stage V
Brand	MAGNI
Length	7620 mm
Width	2540 mm
Weight	16600 kg
Load capacity	5000 kg
Height Elevation	25 m
Maximum range	19 m
Motor Power (KW)	100 kW (136 hp) at 2,200 rpm
Maximum elevation height	24.6 m
Stabilizers	Pivoting
Load capacity at maximum height	2000 kg
Ground clearance	320 mm
No. of gears	44959
Hydraulic system	350 bar
Travel speed	40 km/h
Rotation	360° (continued)
Climate control as standard	Yes
Automatic recognition of accessories	Yes
Ordering	4999