

1350SJP Ultra Series Telescopic Boom Hoist

Referencia: 1350SJP



Description

Moves productivity to a higher altitude

Ability to dominate the work area. The Ultra Series JLG® is up to any challenge. This rugged machine provides the confidence and support needed to handle the jobs you face with the necessary capability.

The uniquely controlled arc regulates speeds at the limits of the working area, so that the operator feels the same speed in all positions for greater comfort.

Standard features

- Low access platform 0.91x 2.44 m (0.91 x 2.44 m)
- Side entrance with folding bar
- Multifunctional operation
- Thumb-operated proportional joystick for maneuvering
- Proportional joystick control of main and swing arm
- Variable speed drive for telescope movement and platform rotation
- 2.44 m articulating jib
- Four-way JibPLUS® jib with horizontal travel up to 180°
- Lateral collection by propulsion in the jib
- 180° powered platform rotation
- Light panel on the platform console with machine status indication
- Load sensing system
- AC power cable to the platform
- Gull-wing covers
- Removable motor tray
- Anti-spark converter
- ADE® control system (Advanced Design Electronic System)
- Hydrostatic transmission
- Four-wheel drive
- 4-wheel steering / 2-wheel steering / crab steering
- Horn
- Double selectable platform capacity (230kg/450kg)
- Removable extendable shafts
- Indicator light and alarm for inclination of more than 5 degrees
- Front oscillating shaft
- Lifting/anchoring brackets
- Hour meter
- Control selector switch at the base with key lock
- Hydraulic load sensing system
- Tool tray on the platform
- 12 V DC auxiliary power supply
- Engine failure alarm/shutdown system
- Selectable slow speed in travel, lift and swing functions
- Protection system JLG® SkyGuard

Accessories and options

- Platform with 0.91 m x 1.83 m sliding bar side entrance
- Self-closing inward swing door 0.91 m x 1.83 m (0.91 m x 1.83 m)
- 13 mm air duct to the platform
- Integrated 4,000 W generator
- SkyPower® package with integrated 7,500 W generator
- SkyWelder® 250 A welder on the platform
- SkyGlazier® package for glass and panel support
- Nite-Bright® Package
- Motion alarm
- Lighting package
- Flashing amber flashing headlight
- European type plug and socket
- Harsh Conditions Package
- Hydraulic oil coolant
- Anti-spark converter
- Proximity sensor Soft Touch for 0.91 m x 1.83 m platform
- Soft Touch proximity sensor for 0.91 m x 2.44 m platform
- Airborne Signal Beacon (ILOS)
- Polar climates package
- Generator hour meter
- Biodegradable synthetic hydraulic oil
- Platform working lights
- Front and rear lights
- Custom color
- 445/65-24 solid tires

Technical sheet

Engine type	Deutz TCD 2.9 L4
Machine type	Telescopic platforms
Turning radius	4.39 m / 6.86 m
Weight	20400 kg
Load capacity	450 kg
Height Elevation	43,3 m
Motor Power (KW)	55.4 kw
Gradeability	45 %
Platform Height	43,3 m